



地址：中国天津
邮编：301600
网址：www.huayuanwire.com
邮箱：yxs@tjhygy.com.cn



HUAYUAN GROUP
TIANJIN HUAYUAN INDUSTRY (GROUP) COMPANY




Group Introduction 集团简介

天津华源集团位于天津市静海区，企业创建于1992年，下属十一个企业，三个“省市级企业技术中心”，拥有总资产15亿元人民币、企业员工2800余人，其中高级工程师、工程师、助理工程师100余名，拥有十大系列产品，年生产及加工能力80万吨以上，70%以上销往全球70多个国家和地区。自创办以来，始终坚持“创业、树人、精品、诚信”的华源精神，始终坚持“做好生意、做好合作的生意、做好合作伙伴的生意”的经营理念，受到了国内外广大用户的好评和信赖。是全国线材制品行业协会常务理事单位，中国企业联合会常务理事单位。

体系保证

- ISO9001 质量管理体系认证
- IATF16949 质量管理体系认证
- ISO14001 环境管理体系认证
- 日本 JIS 产品认证
- 韩国 KS 产品认证
- 澳大利亚 ACRS 产品认证



HUAYUAN GROUP

Tianjin Huayuan Group ("Huayuan") is located in the Jinghai District, Tianjin, was founded in 1992 and is now 11 manufacturing enterprises, 3 provincial marketing companies and a municipally recognized technical center. It has total assets of 1.5 billion RMB and over 2,800 employees, among whom there are more than 100 senior engineers, engineers and assistant engineers. With ten categories of products. The annual production and marketing capacity is more than 800,000 tons, of which an estimated 70% is exported to more than 70 countries and regions. Since its inception, Huayuan has committed itself to our founding principles, "Business Establishment, People Cultivation, Superfine Products and Sincere Service". All Huayuan employees adhere to the same core ideas and values. "Do proper business properly, Do cooperative business cooperatively and Do mutual business mutually". As a result, the Huayuan name is well recognized and trusted worldwide. At the same time is also an executive member of the National Wire Products Industry Association and the China Enterprise Confederation.

Assurance System

- ISO9001 quality management system certification
- IATF16949 quality management system certification
- ISO14001 environmental management system certification
- Japan JIS certification
- Korea KS certification
- Australia ACRS certification



HUAYUAN GROUP

Galvanized Steel Wire for Livestock and Poultry

畜牧焊网用镀锌钢丝



热镀锌钢丝

线径MM	Q195 抗拉强度 MPA	Q235 抗拉强度 MPA	上锌量 G/M ² 不小于	铝含量 % 不小于 Aluminium%
1.8	600-800	700-900	250	--
2.0	600-800	700-900	260	--
2.2	600-800	700-900	275	--
2.5	600-800	700-900	275	--
3.0	600-800	700-900	275	--
3.5	600-800	700-900	275	--
4.0	550-750	600-800	275	--
5.0	550-750	600-800	275	--

原材料: Q195/Q235

包装: 50-1000 公斤 / 卷

热镀锌钢丝采用优质低碳盘条经过拉拔、酸洗、镀锌等工艺生产，上锌量高，耐腐蚀，表面光亮光滑，铁丝强度均匀，易焊接，抗氧化、坚固耐用。

Material: Q195/Q235

Packing: 50-1000kg/coil

Hot dipped galvanized wire is produced by high quality low carbon wire rod with drawing, pickling, galvanizing etc. It has heavy zinc coating, corrosion resistance, bright and smooth surface, uniform tensile strength, easy welding, anti-oxidation and durable.

Zinc-5%/10% Aluminum-Mixed Mischmetal alloy-coated low carbon steel Wire for Livestock and Poultry

畜牧焊网用锌铝合金钢丝



锌-10%铝-混合稀土合金镀层低碳钢丝（简称：锌铝合金钢丝）具有很强的抗腐蚀性能和自修复能力，其产品的抗腐蚀性能是普通纯镀锌钢丝的5-10倍。该产品的延展性及可变形能力极强，易焊接且焊接牢固，能经得起在强力变形工艺条件下缠绕、弯曲的考验，而不必担心锌层的龟裂与脱落。

该产品广泛用于畜牧养殖行业！随着焊接设备的更新换代与不断升级，焊点牢固性和焊点防腐性能等问题都得到了很好的改善解决。经过多年的实践证明此生产工艺已经成熟，完全可以替代先焊后镀传统老工艺。不仅整体降低了网片制造成本，而且外观更加整齐光滑。

Zinc-5%/10% Aluminium alloy-coated low carbon steel Wire (Abbreviated as Zn-Al alloy steel wire) has strong corrosion resistance and self-healing capacity, and its corrosion resistance capacity is 5-10 times that of common pure galvanized steel wire. The product has strong ductility and deformability, is easy to weld and welds firmly, and can withstand the test of wrapping and bending under the condition of strong deformation process, without worrying about the cracking and shedding of zinc coating.

This product is widely used in animal husbandry industry, with the upgrading of welding equipment, the fastness and anticorrosion of weld point have been solved. After many years practice, it has been proved that the production process has matured and can replace the traditional process of weld before galvanizing, it not only reduces the manufacturing cost, also make the appearance more neat and smooth.



5% 锌铝合金镀锌钢丝

线径MM	Q195 抗拉强度 MPA	Q235 抗拉强度 MPA	上锌量 G/M ² 不小于	铝含量 % Aluminium%
1.8	600-800	700-900	250	4.2-6.2
2.0	600-800	700-900	260	4.2-6.2
2.2	600-800	700-900	275	4.2-6.2
2.5	600-800	700-900	275	4.2-6.2
3.0	600-800	700-900	275	4.2-6.2
3.5	600-800	700-900	275	4.2-6.2
4.0	550-750	600-800	275	4.2-6.2
5.0	550-750	600-800	275	4.2-6.2

10% 锌铝合金镀锌钢丝

线径MM	Q195 抗拉强度 MPA	Q235 抗拉强度 MPA	上锌量 G/M ² 不小于	铝含量 % Aluminium%
1.8	600-800	700-900	250	10
2.0	600-800	700-900	260	10
2.2	600-800	700-900	275	10
2.5	600-800	700-900	275	10
3.0	600-800	700-900	275	10
3.5	600-800	700-900	275	10
4.0	550-750	600-800	275	10
5.0	550-750	600-800	275	10

原材料:

- A、优质低碳钢 Q195、Q235
- B、锌-10%铝-混合稀土合金镀层

包装: 50-1000 公斤 / 卷

Material: Q195/Q235

Packing: 50-1000kg/coil

